

Date: May 23/05

Well Owner: [redacted]  
Address: 31 Redwood St  
Whitehorse, Yukon Y1A 4B2  
Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Contractor: Cathway Water Resources  
Address: Box 21048 White.  
Phone: 668-7208 Fax: 668-7208  
Driller: [redacted]

**General Information**

Well Location:  At owners address  Other  
Lot # 6 Soapberry Lane  
Water Quality:  Good  Poor, why \_\_\_\_\_

Water Analysis:  chemical  Biological  none

Comments: \_\_\_\_\_  
Taste: \_\_\_\_\_

Water use:  domestic  Stock  Garden  
 Irrigation  Heat pump  Industry  
 Community supply; number of connections \_\_\_\_\_  
 Other \_\_\_\_\_

Aquifer:  Rock  Sand and gravel

Well Capacity

Capacity:  dry hole  Inadequate  
 Satisfactory for proposed use

Capacity test:  Bail test  Air lift  Pump test

Length of test \_\_\_\_\_ minutes Rate: \_\_\_\_\_

Water level at start: \_\_\_\_\_

Drawdown at end: \_\_\_\_\_

Estimated well capacity: \_\_\_\_\_

Was a water sample taken at end of test?  Yes  No

**Final well completion**

Cover on casing  Welded plate  Pitless adaptor  
 Aluminium cover  Well seal

Casing:  above ground  In pit  In old dug well

Is casing sealed?  Yes  No

If Yes, describe: \_\_\_\_\_

Is site protected from obvious hazards, ie. poor drainage, grazing animals, buried fuel tanks, etc.  Yes  No

If no, what can be done? \_\_\_\_\_

If well location cannot be described from a road address,

please sketch approximate location on reverse side of file copy of well record or attach separate sheet.

Well Log		Metres <input type="checkbox"/>	Feet <input type="checkbox"/>
From	To	Description	
0	6	sand	
6	15	silty sand & clay	
15	153	clay	
153	174	silty sand (heaved)	
174	205	silty sand & clay	
205	208	clay	
208	216	sandy gravel w/ water	

\* If drilling is in rock, note depth of fractures which make water.

**Well Construction**

Surface Casing: Diameter \_\_\_\_\_  
Length 21'11" Stick up 30"

removed  Left in place

Well Casing: Diameter 6"

Length 21'11" Stick up 30"

Wall thickness: .250"

Casing shoe  yes  no

Completion:  well screen  slotted pipe  
 open end  other

Well screen:  stainless  galvanized steel  
 plastic

from 210'8" to 215'10" slot width 10 slot

from \_\_\_\_\_ to \_\_\_\_\_ slot width \_\_\_\_\_

Design based on:  sieve analysis  
 estimated slot size

Other screen data: \_\_\_\_\_

Development method:  surge  bail  air  
 water jet  pump  other \_\_\_\_\_

Static water level below ground: 68'

flowing Rate: \_\_\_\_\_