



LORAX
ENVIRONMENTAL

MW14-05B / BH11 / CFD-0455

(Page 1 of 1)



Drilling Started : Sep 17, 2014
 Install Completed : Sep 20, 2014
 Drilling Method : Diamond / HQ
 Drilling Company : CYR Drilling Ltd.
 Supervised By : [REDACTED]

Northing Coord. : 6,972,998.51
 Easting Coord. : 579,694.92
 Ground Surface : 1270.3 m amsl
 Logged By : Kaminak
 Checked By : [REDACTED]

Coffee Creek Gold
 Project #: A362-4

Depth (m)	Elev. (m amsl)	DESCRIPTION	RQD (%)	Fracture = Fr Fault = Ft	Packer Test Interval (mbgs)	K (m/s)	Depth (m)	Well: MW14-05B Elev.: 1270.9 m amsl (TOC)
0	1270	GRANITE Fresh coarse grained granite, patchy clay alteration of feldspar, typically associated with fractures, weak to moderate fracture controlled limonite. See MW14-05A for details					0	<ul style="list-style-type: none"> Surface Monument & Casing stickup Bentonite Pellets 2" Sched. 80 PVC Cement Grout Bentonite Pellets Suspected cave-in Filter Sand Screen
20	1250						20	
40	1230						40	
60	1210			N/A	N/A	N/A	60	
80	1190						80	
100	1170						100	
120	1150						120	
140	1130						140	
160	1110						160	
180	1090	EOH @ 179.5 m N/A: Borehole not packer tested or logged for structure					180	
200							200	

03-04-2016 P:\A362-4 (Coffee Gold Project - Hydrogeology)\Data\BH Logs\Quicklog\2014\MW14-05B.bor