## W 55 **Impact Drilling** 867-668-6943 WELL FURM 6" - 12" • Water Wells • Pump Installation • Exploration • Dual Rotary Air Rig • Pilings Owner name: City / Town: Mailing address: Prov. / Terr. Postal Code \_\_\_\_\_ City / Town \_ Well Location Address: Street No. Whie OR Legal description: Lot \_ OR PID: \_ AND Description of well location (attach sketch if nec.): \_\_\_\_ 60 UTM Harring: 67198-1950 UTM Northing: 8500812 Cm Latitude: NAD 83: Zone: Longitude: \_ Method of drilling: □ air rotary ☐ dual rotary □ cable tool □ mud rotary □ auger □ driving □ jetting □ other (specify) \_ Orientation of well: ☑ vertical □ horizontal Ground elevation \_ 6 ? 2 ... \_ ft (asl) Method: \_\_\_\_\_ Water supply wells, indicate water use: □ private domestic □ water supply system □ irrigation □ commercial or industrial other (specify) . LITHOLOGIC DESCRIPTION Surficial Material **Bedrock Material** Color Hardness Water Content Observations (e.g. other geological materials (e.g. boulders), est. water bearing flow (USgpm), or closure details) From To Dry Mois Wet High Lost Not a ft (bgl) ft (bgl) 000000 Dodrock **SCREEN DETAILS CASING DETAILS** Slot Drive From Dia Dia From **Thickness** Type Casing Material / Open Hole Size Shoe ft (bgl) ft (bgl) in ft (bgl) ft (bgl) in 638 1 teck 62 219 p.R Bandonte Intake: Screen Open bottom Uncased hole Depth. Surface seal: Type -Method of installation ☐ Poured ☐ Pumped 10 in Thickness Screen type: Telescope Pipe size

Screen material: Stainless steel Plastic Other: Depth. Backfill: Type \_ Screen opening: ☐ Continuous slot ☐ Slotted ☐ Perforated pipe Liner: □ PVC □ Other (specify): \_ Screen bottom: Bail Plug Plate Other: \_\_in Thickness From 20 ft (bgl) To 24 oft (bgl) \_\_ ft To: \_\_\_\_\_\_ ft Thickness: \_ Filter pack: From \_ Type and size of material: \_ft (bgl) To \_ Perforated: From \_ **FINAL WELL COMPLETION DATA DEVELOPED BY** Total depth drilled: 2% ft Finished well depth: \_ ☑Air lifting ☐ Surging ☐ Jetting ☐ Pumping ☐ Bailing ft (bgl) Total duration: Other (specify): \_ Final stick up: Depth to bedrock: ft (bgl) Notes: \_ USgpm ft (bgl) Estimated well yield **WELL YIELD ESTIMATED BY** USgpm, or Artesian pressure: \_ ☐ Pumping ☐ Air lifting ☐ Bailing ☐ Other (specify): Type of well cap: Locking hrs . USgpm Durtation: \_ Rate: \_ Where well ID plate is attached: ft (btoc) \_ft (btoc) Pumping water level: . SWL before test: \_\_\_ **WELL CLOSURE INFORMATION OBVIOUS WATER QUALITY CHARACTERISTICS** ☐ Fresh ☐ Salty ☐ Clear ☐ Cloudy ☐ Sediment ☐ Gas Reason for closure: \_ Method of closure: ☐ Poured ☐ Pumped Water sample collected: Colour / Odour: \_ Backfill material: Sealant Material: WELL DRILLER (print clear Details of closure: \_ Name (first, last): . Consultant (if applicable; name & company) DATE OF WORK (yvyy/mm/dd) July 2016 completed July 2016 Signature of Comments:

PLEASE NOTE: The information recorded in this well report describes the works and hydrogeologic conditions at the time of construction, alteration or closure as the case may be. Well yield, well performance and water quality are not quaranteed as they are influenced by a number of factors, including natural variability, human activities and condition of the works, which may

na a santa da santa d

WHITE: CUSTOMER COPY | YELLOW: YTG COPY | PINK: DRILLER COPY

| Driller Responsible