WELI	FOR	RN	٠.					a (E	xpl	ora	atio	on	• [Dua	al F	Rot	ary	Ai	r R	ig	• F		ng:	S			sheet _		(of _	
Owner n	amo: 71															ŀ	free		74	-		4				_		_	_			_						_								
Mailing	allio																_	itr	77	-	n	(:		1			-)	. /7			V	T		D.		-1.0	Code				
Well Loc	address: ation Add	droc		Ctr	.00	+ N/	_	L	7÷	10	a	1_	1)		Ctr	oot	no	/ I	OW	1	h	10-	4	K	1.		1	.4	10	_ 1	101	. / I	en.	-	•,	1	11	۲(ام	S	ai C	.oue	-			
(ID) Long	al descrip	ui Ga	. I	oli ot	66	LIVE	U		,	Dia	<u></u>	1	_			out		IId	1111	_		4	D	las	ائد	10	in	α_	11	16		_ 0	ity /	101	WII			_	*,	0			-			
												rip	tio	n c	of v	rell	lo	cat	tio	n (a	tta	ch	sk	ceto	ch if	ne	ec.):	:_							2							-				
NAD 83:	Zone:				_					[AND)	UT	M	Eas	stin rthi	ıg:	_	0	8	3	19	2	2 5	3 -	8	r	n n	0	R																
Mothod	of drilling	г	٦,	ir r	oto	m .		d	al r	otor	a, I		-				3	_								_	_																			
Orientat	of drilling ion of we	j. L		n I	ica	ıy		hor	di II	otal	уι	_ (Cro	idu	4.0	lou	L atio	ייי דו די	iuc	110		ا ک	8	au	iye		_ (ft /	ıng (aa	, L	⊒ je Mot	hoc	g.		uie	(8	pe	CII	() —	-							
•	well:						ш	HOI	120	IIIai)	uic	un	u e	iev	auo	111 _			Ť	-	U	-				. 11.	(as	ii)	wei	1100	1			_											
	pply wells					iter	us		_	oriva					. [Jv	vat	er s	sup	ply	sy	/ste	em	1	⊐ji	rrig	atio	on] c	mr	ner	cial	or i	ind	ust	ria	1	. pr							
LITHOL	nele ne	ent	N	TIC) RE	VS RS		(9 k))U16	1 10	her	, II Y	<i>)</i> —													W 17	1488					11112						1911						10.0	
LITHUL	JGIG DE	C DESCRIPTION Surficial Material Bedrock Material													5/8	辨級	Co	lor	ection.			100	ŀ	laro	ine	SS	s Water Content								Observation											
				T	T	T				-	Т	T	T				<u> </u>	1	ğ								Т			<u> </u>		T	T	+	Ť	1			T	T	┪	(e.g	, oth	er ge	olog	ical
From ft (bgl)	To ft (bgl)	Clay	Ħ			and with day/siit	and, fine-med	and, med-coarse	Sand with gravel	Siltstone/Shale	andstone	Propodiorito	alairouoi ile	imestone	lasalt	olcanic	cystalline		Other Surficial Bedro	led)range	-	Srown	Slack	Light Grey	Ship	2000	ireen	Dark Grey	ery Hard	lard	Jense / Stiff	dsoo	No.		Aoist	Vet	ligh Production	and officer lotters	ost circulation	Vot available	est.	water Sgpm	r bea	ring clos	
0	68	0	O	C	(b	O.	0	0	0	C) (0	0	0	C) (0											0	O	C	86) @		0	0	0	(5	0				-	
68	95																																									Wo	uk	2 n	0	ł
0	·									0 0 0 00 0 0 0																															4					
95	150																																								39pm dirt			Tu		
150	170										00000																													11			-			
177	228	_		-	_	_		_	_	-	$\overline{}$	\rightarrow		\rightarrow			-	_	$\overline{}$		-		$\overline{}$		_	-	_	_		_	•	_	_	0	_	$\overline{}$		-	_	$\overline{}$						
228	233																																	0												
	_ y//,																																	0												
																																		0												
	1 A		-		_	_		_		-		$\overline{}$	_	_		-	$\overline{}$	_	$\overline{}$		-	$\overline{}$	$\overline{}$		-	$\overline{}$	_	_		_	-	_		_	_	_		_	_							
CASING	DETAILS										1							11.		ed a			_	OOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOO																						
From ft (bgl)	То		Dia in			Casing Ma			terial / Open Hole					Т	Wall Thickness in				Drive Shoe			Fror ft (bo		m	n		To t (bgl)		Dia in			Туре							Slot Size							
0	229	6	65%			54			de						7 ,	a	9		Pik		2	1	22		Ť	3.	3.	3	10	6		(4)	-											1	12	
									_,								_	•	T	•		_	2	3	33	,	2:	3	7		6															12
																																							ř						_	
			٠, ،	3	Ļ	_									1				1	,_			L												_						,					
Surface	seal: Type		_	6	V	7	-6	200	-	OV	16	> 4	2.		. [)ep	th.				_1		Ir	nta	ke:		Sc	ree	en		0p	en	bot	om		J	Jno	ase	ed	ho	le					
Method	of installa	tion		P	our	ed] P	um	ped				Th	nick	nes	SS _		1	6	_ i	n	S	Scre	een	typ	e:	Ø	₹ Te	les	сор	е		Pipe	s	ze										
Backfill:	Туре		S	-						1					. [)ep	th .			_	f	ft	S	Scre	een	ma	ater	rial	: E	St	ain	ess	ste	eel		1 P	las	tic]()the	er:				-
Liner: □	PVC 🗆 C	the	r (s	pec	cify):_														-		_																				orated				
	r																				_ ir	n																				er:				
From	f	t (b	gl)	To .				f	t (b	gl)																																ness:_				
	ed: From .									_		ft	(bg	l)																																
					_	_																_	_																	and the same			Danie I			

FINAL WELL COMPLETION DATA DEVELOPED BY Finished well depth: ☑Air lifting ☐ Surging ☐ Jetting ☐ Pumping ☐ Bailing Other (specify): _ Total duration: ft (bgl) Final stick up: _ Depth to bedrock: Notes: _ Estimated well yield. USgpm SWL: ft (bgl) WELL YIELD ESTIMATED BY USgpm, or Artesian pressure: Artesian flow: _ ☐ Pumping ☐ Air lifting ☐ Bailing ☐ Other (specify): Type of well cap: Well disinfected: ☐ Yes ☐ No . USgpm Durtation: . . hrs Rate: _ Where well ID plate is attached: _ ft (btoc) ft (btoc) SWL before test: _ Pumping water level: **OBVIOUS WATER QUALITY CHARACTERISTICS** WELL CLOSURE INFORMATION Reason for closure: . ☐ Fresh ☐ Salty ☐ Clear ☐ Cloudy ☐ Sediment ☐ Gas Method of closure: ☐ Poured ☐ Pumped Colour / Odour: . Water sample collected: Backfill material: Sealant Material: WELL DRILLER (print clear) Details of closure: Name (first, last): Consultant (if applicable; name & company) DATE OF WORK (yyyy/mm/dd) Oct 2015 Signature of PLEASE NOTE: The information recorded in this well report describes the works and hydrogeologic conditions at the time of construction, alteration or closure as the case may be. Well yield, well performance and water quality are not quaranteed as they are influenced by a number of factors, including natural variability, human activities and condition of the works, which may

and the second control of the second control

WHITE: CUSTOMER COPY | YELLOW: YTG COPY | PINK: DRILLER COPY