WEL	L FUF	KM																- 69 alla			-E	xpl		tio			_			ry	Aiı	o Ri	g•	Pil	ing	S			sheet	of	
Owner r	ame																	870	-		_			_						_			_		_		_				
				· suf		, j		91		2.0			8 -			C	itv	/ Tov	wn				().	-16		ė			Pı	rov	/ T	err	4	/ -	t	. Po	nets	al C	ode.		
Well Lo	ation Ad	dres	s: S	Stre	et I	No.	_	0	90	5-	2				Str	reet	na	me_		·Y	Μ	in	10	R	d					Ci	v /	Tov	/n _	ľ	T	· W	J	, h	Code	γ	V
OR Leg	al descri _l	ption	: Lo	t_			_	_	PI	an	_				_ [).L.	_		_		. 8	Bloc	u k_				_	· .			.								0		
OR PID:			_		_		- (ANI	9	De	scr	ipti	on	of v	vel	l lo	cat	ion	(att	ach	sk	cetc	h if	nęc	:.):		1	5 1		L	e 1	+		a	7-1			5	od lo us	(-ev	<u>'</u> S
A	ppro	*	2	<u></u>	_	(CM	-	_	1.0	1.0		91	d	e		ct (-	h	U	17	e		4	300	>	4	2	ΩV	V	4	6	1	4	3	1	ra	ul	. Covi	4. C	<u></u>
NAD 83:	R PID: AND Description of well location (attach												_				_m	1	OR)	La	titu	de	-	_	_			_												
Method	of drillin	n. F	Tair	rot	arı		Let	ual	rot	anı	_	U Log	l M	too	rth L C	ing 7 n	: _	roto		П	-		_	1 4-	_m	1	_	:-4	Lo	ngi	tuc 1 -4	le: _	/	!6	٠,٠		-			-	
Oriental	ion of we	ell: C	l ve	rtica	al		ho	orizo	ont	al y	G	rou	nd (elev	atio	חוב	iuu	TULC	пу	Ч	au	igei	_	u ui	IVII ft (s	ıy ı asl)	Ц М	A	UH.	1	2	ner	(sp	ecii	y) _	_					
Class of																									, ,			Q.	۷ ^u .			-					ÿ.				
Water su	pply well	s, inc	licat	e w	ate	er u	se:		pri	vat	e di	ome	sti	c [J	wate	er s	upp	ly s	syste	em] ir	riga	tio	n I		cor	nm	erc	ial	or ir	ndus	stria	ıl						-
	8		_						oth	ier	(sp	ecif	y) _																_				10								
LITHOL	OGIC DE	SCR	IPT	101	1			,							710-7		la lati Vision		,																						
	Sunticial Material Sand with day/sift Sand with gravel Other Sunticial Bedrock Sand with gravel Sand with															Col	or	20000	311,1890		Hardness						Wa	ter	Con	ten	nt	T	Obser	Observations							
to the					_					T							J.	5	Ī								T									Т	T		(e.g. other materials (e		
					day/sil	med	coarse	ıravel	-	ale		m					ial Re													_					tion	pon			est. water l	bearin	ng flow
From	То				with	, fine-	med.	with	1	one/si	stone	odiorit	stone	ı.	nic	alline	y V			e de	_		Grey		_	Grev	1	lard		e / Stif	•				Produc	ircula		vailabl	(USgpm), det	, or clo tails)	osure
ft (bgl)	ft (bgl)	Clay	莣	囯	Sand	Sand	Sand	Sand	1	Silts	Sand	Gran	Lime	Basa	Volca	Cryst	, att	Red		D C	Prow	Black	Light	Blue	Green	Dark	Von	very	Hard	Densi	Loose	Da	Moist	Wet	High	Lost		Nota			
2	20	0	0	0	0	O	0	e	710) (0	0	0	0	0	0	C) O) () (2	0	0	0	0	C) [0	0	0	9	0	0	0	0) [(0			
20	80																	0																							
30	7/																																								
-																																									
																		0																							
		0	0	0	0	0	0	0		0 (0	0	0	0	0	0	C	0) (0)	0	0	0	0	С	()	0	0	0	0	0	0	0	0) (0			
																		0																							
O A O IVIO	DETAILO	TO :	O :	O :		(SISCHE)	<u> </u>		1			O :		CO C		TO THE REAL PROPERTY.	i C		1								T	J : 1		O .	Ų.			<u>;</u>	100	<u>;</u> O	/ (CAN DESCRIPTION	\$10615 V.D	
CASING	CASING DETAILS														S	CREEN DETAILS																									
From ft (bgl)	To ft (bgl)		ia n	(Cas	sing	Ma	ater	ial	al / Open Hole				Wall Thickness in				Drive Shoe		From ft (bgl)		To ft (bgl)		Dia in				Туре									Slot Size				
0	27	6	(5	re	J	Q					219			1	Pik									. 0			>>>									25				
								-											_	,			п							L											
														\dashv	_			_						┡	_	-					_			_							
Surface	Surface seal: Type Depth 5 ft														-	dal.	Г	7.0		-	_	7.0		<u> </u>				Una		d b	-	_									
	Method of installation ☐ Pumped Thickness in															tak cree				-									ase	a n	IOIE	3									
	Backfill: Type Depth ft																								5)			tic		Ot	ther	r:									
	Liner: PVC Other (specify):													S	cree	en c	per	ning	g: C](Con	tinu	ıðn	s sl	ot I		Slott	ed		Pe	erfo	rated pipe									
CONTRACTOR SECTION	Diameter in Thickness in													0.1																		r:									
	From ft (bgl) To ft (bgl) Perforated: From ft (bgl) To ft (bgl)													Filter pack: From ft To: ft Thickness: ir Type and size of material:														in													
renorati	ou. MUIII .			_ 1	(0	yy)	IU.		_	_	_ 11	(ng	"						_		_	_	-	-						_		_									
The second second second	DEVELOPED BY											F	INA	LV	/EL	L C	ON	PL	ĘŢ	ON	DA	TA							5514 3	- Ctú	6										
	ting 🗆 S	_									-											otal																	1:		
	oecify):						_	_	_	27	Tot	tal c	lura	atio	1:_	_	_		_h	ırs		inal							•					pth	to b	edr	roc	k:.	-15		_ft (bgl)
	ELD EST												Y				115	a period			s	WL:	_							_ft	(bg	1)							d		
																																	US	gpn	1, 01	Arl	tes	sian	pressure: _		ft
	oing 🗖 🛱																		1	hrs	T	rtes	of	wel	l ca	ıp: _		_	_		. 1	1							☐ Yes ☐ No		
																					1	Vhei																			
	SWL before test: ft (btoc) Pumping water level: ft (btoc) OBVIOUS WATER QUALITY CHARACTERISTICS										_	/EL			-	_	-			ter skilwards		S. College Street							in the part		Sin Li										

PLEASE NOTE: The information recorded in this well report describes the works and hydrogeologic conditions at the time of construction, alteration or closure as the case may be. Well yield, well performance and water quality are not quaranteed as they are influenced by a number of factors, including natural variability, human activities and condition of the works, which may change over time.

Water sample collected:

☐ Fresh ☐ Salty ☐ Clear ☐ Cloudy ☐ Sediment ☐ Gas

Colour / Odour: __

Name (first, last): _

Signature of

Driller Responsible

WELL DRILLER (print clearly

Consultant (if applicable; name & company) _

Reason for closure: .

Sealant Material:

Details of closure: _

Comments: _

DATE OF WORK (yyyy/mm/dd)

Oct 16

Method of closure: ☐ Poured ☐ Pumped

WHITE: CUSTOMER COPY I YELLOW: YTG COPY I PINK: DRILLER COPY

0416

Backfill material:

Completed .