WELL FORM

Impact Drilling 867-668-6943

| choot | of |
|-------|----|

6" - 12" • Water Wells • Pump Installation • Exploration • Dual Rotary Air Rig • Pilings

*Insufficient into To locate Will

| | _ | |
|--|------|--|
| Mailing address: City / Town: Prov. / Terr Postal Code | | |
| Well Location Address: Street No. | | |
| OR PID: AND Description of well location (attach sketch if nec.): Right Side | | |
| house about the of way down Approx 8 out them cid | 2_ | |
| NAD 83: Zone: MOR | - | |
| Method of drilling: ☐ air rotary ☐ dual rotary ☐ cable tool ☐ mud rotary ☐ auger ☐ driving ☐ jetting ☐ other (specify) | | |
| Orientation of well: vertical horizontal Ground elevation from the fit (asl) Method: | | |
| Class of well: | | |
| Water supply wells, indicate water use: ☐ private domestic ☐ water supply system ☐ irrigation ☐ commercial or industrial | | |
| other (specify) | | |
| LITHOLOGIC DESCRIPTION | | |
| Surficial Material Bedrock Material Color Hardness Water Content Observations (e.g. other geologic | cal | |
| ### (e.g. other geologic materials (e.g. bould start bearing fi | | |
| Learning of the page of the pa | | |
| Limestone Sand with clay(silt Sand stone Sand, med-coarse Sand, med-coarse Sand, med-coarse Sand stone | | |
| 0 9 00000000000000000000000000000000000 | | |
| 19 23 00000000000000000000000000000000000 | ek | |
| 27 000000000000000000000000000000000000 | | |
| 49 49 000000000000000000000000000000000 | 1 | |
| | | |
| | | |
| 000000000000000000000000000000000000000 | | |
| 000000000000000000000000000000000000000 | | |
| CASING DETAILS SCREET | | |
| From To Dia Wall Drive From | Slot | |
| ft (bgl) ft (bgl) Casing Material / Open Hole Thickness Shoe ft (bgl) 105 D 11 | Size | |
| 0 58 656 Steel 219 D.K | | |
| | | |
| | | |
| Surface seal: Type Bankonice Depth 15 ft Intake: 25 m | - | |
| Method of installation ☐ Poured. ☐ Pumped Thickness in Screen | | |
| Backfill: Type Depthft Screen | | |
| Liner: Diameter in Thickness 250 in Screen Screen | | |
| From 19 ft (bgl) To 478 ft (bgl) | in | |
| Perforated: From ft (bgl) To ft (bgl) Type and size of material: | | |
| DEVELOPED BY FINAL WELL COMPLETION DATA | | |
| Air lifting Surging Jetting Pumping Bailing Total depth drilled: 198 ft Finished well depth: 198 ft | | |
| Other (specify): Total duration: hrs Final stick up: in Depth to bedrock : ft | | |
| Notes: SWL: ft (bgl) Estimated well yield US | | |
| Pumping P Air lifting Bailing Other (specify): | ft | |
| Rate: USgpm Durtation: hrs Type of well cap: Well disinfected: | | |
| SWL before test:ft (btoc) Pumping water level:ft (btoc) Where well ID plate is attached: | | |
| OBVIOUS WATER QUALITY CHARACTERISTICS WELL CLOSURE INFORMATION Reason for closure: | | |
| ☐ Fresh ☐ Salty ☐ Clear ☐ Cloudy ☐ Sediment ☐ Gas Colour / Odour: Water sample collected: ☐ Method of closure: ☐ Pumped | | |
| WELL DRILLER (print comments and provided an | | |
| Name (first, last): | | |
| Consultant (if applicable; name & company) | | |
| DATE OF WORK (yyyy/mm/dd) | | |
| Started: Man 2010 Completed Man 2010 | 3 | |
| Signature of Driller Responsibl Comments: | | |

PLEASE NOTE: The information recorded in this well report describes the works and hydrogeologic conditions at the time of construction, alteration or closure as the case may be. Well yield, well performance and water quality are not quaranteed as they are influenced by a number of factors, including natural variability, human activities and condition of the works, which may change over time.