

| | | | | | | |
|-----------------------------------|---|--------------------------------------|---|-----------------------------------|---|-------------------------------|
| Carcross WTF- 15MW01 Installation | Yukon Government - Community Services | BOREHOLE NO: 15MW01 | | | | |
| km 109.8 on South Klondike Hwy | | PROJECT: ENVH2003164-01 | | | | |
| Carcross, Yukon | | | | | | |
| SAMPLE TYPE | <input checked="" type="checkbox"/> DISTURBED | <input type="checkbox"/> NO RECOVERY | <input checked="" type="checkbox"/> SPT | <input type="checkbox"/> A-CASING | <input type="checkbox"/> SHELBY TUBE | <input type="checkbox"/> CORE |
| BACKFILL TYPE | <input checked="" type="checkbox"/> BENTONITE | <input type="checkbox"/> PEA GRAVEL | <input type="checkbox"/> SLOUGH | <input type="checkbox"/> GROUT | <input type="checkbox"/> DRILL CUTTINGS | <input type="checkbox"/> SAND |

| Depth (m) | SOIL DESCRIPTION | SAMPLE TYPE | NOTES & COMMENTS | Depth (ft) |
|-----------|---|-------------|----------------------------|------------|
| 0 | CLAY - silty, damp to wet, soft, medium to high plastic, brownish grey, moisture increasing with depth | | Pipe stickup = 0.80 metres | 0 |
| 1 | | | | |
| | - trace medium to coarse subangular gravel, wet, high plastic | | | 5 |
| 2 | | | | |
| 3 | <p>END OF BOREHOLE (2.52 metres) water - dry at completion. Monitoring well installed to 2.44 metres Screen - 0.91 to 2.44 metres Bentonite chips - 0 to 0.61 metres Sand - 0.61 to 2.52 metres Note: Stopped due to auger refusal.</p> | | | 10 |



| | |
|-------------------------|--------------------------|
| LOGGED BY: [REDACTED] | COMPLETION DEPTH: 2.52 m |
| REVIEWED BY: [REDACTED] | COMPLETE: 15/09/08 |
| DRAWING NO: | Page 1 of 1 |