


2010 Monitoring Well Program	CLIENT: YG - Department of Community Services	PROJECT NO. - BOREHOLE NO.
Champagne Landfill	DRILL: Geotech MST-Odex	W23101317-CH-MW02
Champagne, YT	6740222N; 420525E; Zone 8	
SAMPLE TYPE	<input type="checkbox"/> DISTURBED <input type="checkbox"/> NO RECOVERY <input type="checkbox"/> SPT	<input type="checkbox"/> A-CASING <input type="checkbox"/> SHELBY TUBE <input type="checkbox"/> CORE
BACKFILL TYPE	<input type="checkbox"/> BENTONITE <input type="checkbox"/> PEA GRAVEL <input type="checkbox"/> SLOUGH	<input type="checkbox"/> GROUT <input type="checkbox"/> DRILL CUTTINGS <input type="checkbox"/> SAND

Depth (m)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	NOTES & COMMENTS	Monitoring well	Depth (ft)
0	SILT - uniformly graded, damp, loose, yellow brown		G1			0
1						5
2	- some to trace sand, very fine to fine grained sand, medium brown		G2			10
3	- no sand, moist					15
4	- some to trace clay		G3			20
5			G4			25
6	- no clay		G5			30
7			G6			35
8	- trace clay					40
9			G7			45
10			G8			50
11						55
12			G9			60
13	- some to trace sand, very fine to medium grained sand, moist to wet, grey brown		G10			65
14						70
15			G11			75
16	SAND and SILT - uniformly graded, very fine to medium grained sand, saturated, grey brown		G12			80
17	END OF BOREHOLE @ 16.5 m (Hole collapsed to 14.3 m)					85
18	NOTE: These logs reflect disturbed material recovered from drill return. Particle sizes and shapes (particularly gravel) are affected by drilling process. Cobbles and boulders if present are not indicated through this drilling method. Moisture content is effected by the use of air to recover drill material.					90
19						95
20						100

 <b>EBA Engineering Consultants Ltd.</b>	LOGGED BY: BW	COMPLETION DEPTH: 16.5m
	REVIEWED BY: RMM	COMPLETE: 10/21/2010
	DRAWING NO:	Page 1 of 1