



PROJECT: WATSON LAKE SEWAGE OUTFALL LINE		HOLE NO.: T.H. #2		PROJECT NO.: [REDACTED]			
LOCATION: Watson Lake, Yukon Sta. 9+20 (M)		SURFACE ELEVATION: 678.94m					
DRILL: B40 - Hollow Stem Auger							
SAMPLE TYPE: <input checked="" type="checkbox"/> THIN WALLED TUBE		<input checked="" type="checkbox"/> SPLIT SPOON		<input type="checkbox"/> DISTURBED			
		<input type="checkbox"/> NO RECOVERY		<input type="checkbox"/> CORE			
				<input type="checkbox"/> OTHER			
DEPTH (m.)	SOIL DESCRIPTION	UNIFIED SOIL CLASS.	SAMPLE DEPTH (ft.)	WATER CONTENT-% : ●		COMPRESSIVE STRENGTH	
				PLASTIC LIMIT (W _p)	LIQUID LIMIT (W _L)	Unconfined..... ▲	Pocket Penetrometer..... Δ
				20 40 60 80		TSF 2 3 4 5	kPa 100 200 300 400
1	SAND - light brown - fine - dry - compact		2				
2	SILT - grey - some sand, trace gravel, trace clay - sharp contact		4				
3	SAND - grey - gravelly to and GRAVEL - dense		6				
4	SAND AND SILT - light brown - some gravel - fine grained sand - well graded - very dense		8				
5			10				
6	- light brown - some gravel, trace silt - well graded - dense		12				
7	END OF BOREHOLE		14				
8			16				
9			18				
10			20				
11			22				
12			24				
			26				
			28				
			30				
			32				
			34				
			36				
			38				
			40				
		WET UNIT $\frac{kN}{m^3}$ 16 18 20 22 WEIGHT-D P.C.F. 100 110 120 130 140 150		STANDARD PENETRATION: N- <input checked="" type="checkbox"/>			
DEPTH TO WATER:  DEPTH TO SLOUGH: —		COMPLETION DEPTH: 6.4m		DATE DRILLED: November 27/78			
		LOGGED BY: [REDACTED]		DRAWING NO.:			