

Contractor: Hy-Tech Drilling
 Location: Class A Storage Facility
 Coordinates: 414,780 E, 6,818,383 N
 Coordinate System: UTM09 NAD83
 Hole Size HQ3

Drillhole No.: MW16-14S
 Drill Type: Tech 5000 Diamond Drill
 Total Length: 4.5m
 Elevation: 1341 m
 Inclination: -90

Page: 1 of 1
 Date Started: 25 Jul 16
 Date Completed: 25 Jul 16
 Logged by: [REDACTED]
 Reviewed by: [REDACTED]

| DEPTH - (m) | ELEVATION - (m) | GRAPHIC LOG | MATERIAL DESCRIPTION | RUN RECOVERY (%) | SAMPLE NO. | SAMPLE REC. (%) | SAMPLE TYPE | UCS | KEY ROCK MASS PARAMETERS | | | | INSTRUMENTATION / WELL DETAILS | DRILLING NOTES |
|-------------|-----------------|-------------|--|------------------|------------|-----------------|-------------|-----|--------------------------|---------------|-----|-----|--------------------------------|----------------|
| | | | | | | | | | BLOW COUNTS (PER 6") | SPT 'N' VALUE | RQD | RMR | | |
| | | | | | | | | | SPT TEST 'N' VALUES - X | | | | | |
| | | | | | | | | | 20 | 40 | 60 | 80 | | |
| 1340 | | | TOPSOIL (OVBN) (0 to 0,2 m) SILT, some sand, fine grained, poorly graded, medium plasticity, dark brown, soft, massive, wet. (Topsoil) | | | | | | | | | | | |
| | | | SANDY SILT (OVBN) (0,2 to 3,5 m) Sandy SILT, some gravel, fine to coarse grained, angular, moderately well graded, low plasticity, medium greyish brown, stiff, massive, moist to wet. | | | | | | | | | | | |
| 5 | 1335 | | CLAY AND SILT (OVBN) (3,5 to 4,5 m) CLAY and SILT, some gravel, trace fine sand, fine grained, poorly graded, medium plasticity, light to medium brown, stiff, laminated, wet. End of Drillhole: 4.5 m Reached TD | | | | | | | | | | | |
| 10 | 1330 | | | | | | | | | | | | | |
| 15 | 1325 | | | | | | | | | | | | | |
| 20 | 1320 | | | | | | | | | | | | | |

GENERAL REMARKS:

Installed 1,25" monitoring well with 1,5 m screen. Completion zone from 2,72-4,22 m

**BMC MINERALS (NO.1) LTD.
 KUDZ ZE KAYAH PROJECT**

**Knight Piésold
 CONSULTING**

| | | |
|-------------|----------|------|
| Project No. | Ref. No. | Rev. |
| [REDACTED] | 1 | 0 |

FIGURE B1-15

Logging conducted according to the ASTM 2488 standard and the Canadian Foundation Engineering Manual, 4th Edition, 2006.