

DATE DRILLED: September 10, 2017 TOP OF CASING: 245.917 masl GROUND: 246.007 masl NORTHING: 7495139.78 m
 LOGGED BY: [REDACTED] DRILLER: Midnight Sun Drilling EASTING: 549409.91 m
 DRILLING METHOD: Kova D50 w/ Solid Stem Auger (150mm OD), Hollow Stem Auger (274mm OD) and SPT Autohammer and Split Spoon (50mm OD). Truck Mounted. (UTM Zone 10N, NAD83)

DEPTH (mbgs)	SOIL DESCRIPTION	STRATA PLOT	DEPTH (mbgs)	MONITORING WELL DETAILS		Collected Samples (Grab)	VAPOUR READINGS PID (ppm)
0.25	Well-graded gravel with sand (GW), light brown, dry, dense, angular to subangular gravel to 60mm				Flush Mount Steel Casing with 3/8" Allen Fasteners 3/8" Bentonite Chips		
0.50			245.41				
0.75	Silt (ML), dark grey, moist, stiff, low plasticity, trace organics, trace fine sand		0.60				
1.00							
1.25							
1.50							
1.75							
2.00							
2.25							
2.50	wet at 2.41 mbgs						
2.75							
3.00							
3.25							
3.50							
3.75							
4.00							
4.25							
4.50			241.44				
4.75	EOH @ 4.57mbg		4.57				
5.00							
5.25							
5.50							
5.75							
6.00							
6.25							
6.50							
6.75							
7.00							
7.25							
7.50							
7.75							