

SAMPLE TYPE:  GRAB SAMPLE     NO RECOVERY     STANDARD PEN.     75 mm SPOON     CORE BARREL     NW CORE

DEPTH(m)	SAMPLE TYPE	SAMPLE NO	SPT(N)	USC	SOIL SYMBOL	SOIL DESCRIPTION		STANDARD PENETRATION		PERCENT GRAVEL		DEPTH(ft)
						PLASTIC	M.C.	LIQUID	PERCENT SAND	PERCENT SILT OR FINES	PERCENT CLAY	
0.0						SILT - dry to moist, soft to firm, non to low plastic, brownish grey						0.0
1.0												1.0
2.0												2.0
3.0												3.0
4.0												4.0
5.0												5.0
6.0												6.0
7.0												7.0
8.0												8.0
8.5		1				- thin seam of sand and gravel						8.5
9.0												9.0
10.0												10.0
11.0												11.0
11.5		2				SAND AND GRAVEL - some silt, sub rounded particles, well graded, moist						11.5
12.0												12.0
13.0												13.0
14.0		3										14.0
15.0												15.0
16.0												16.0
17.0		4										17.0
18.0												18.0
19.0												19.0
20.0		5				GRAVEL - some sand						20.0
20.3						END OF BOREHOLE @ 20.3 m						20.3
21.0												21.0
22.0												22.0

<b>EBA Engineering Consultants Ltd.</b> Whitehorse, Yukon	LOGGED BY: [REDACTED]	COMPLETION DEPTH: 20.3 m
	REVIEWED BY: [REDACTED]	COMPLETE: 95/01/25
Fig. No:	Page 1 of 1	