



Borehole No: 20BH05

Project: Phase II ESA - Thompson Drive Residential Dev.

Project No: [REDACTED]

Location: Lot 1, Group 575, Plan 50957

Ground Elev: 695.363 m

Watson Lake, Yukon

UTM: 512848 E; 6664086 N; Z 9

| Depth (m) | Method | Soil Description | Sample Type | Vapour readings (ppmv) | Notes and Comments | Elevation (m) |
|-----------|------------------|---|-------------|------------------------|--------------------|---------------|
| 0 | | | | 1 2 3 4 | | |
| 1 | Solid stem auger | GRAVEL - sandy, trace silt, occasional to trace cobbles, well graded, dry, brown, fine to coarse sand, fine to coarse subrounded gravel | | | | 694 |
| 2 | | - (Gravel - 25%; Sand - 64%; Silt & Clay - 11%) | | | | 692 |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | - occasional cobbles | | | | 690 |
| 6 | | | | | | |
| 7 | | SAND - trace to some gravel, trace silt, well graded, damp to moist, brown, medium to coarse sand, fine to coarse gravel | | | | 688 |
| 8 | | | | | | |
| 9 | | | | | | |
| 10 | | - coarse sand, fine gravel | | | | 686 |
| 11 | | | | | | 684 |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | - (Gravel - 19%; Sand - 75%; Silt & Clay - 6%) - trace fine gravel | | | | 682 |
| 15 | | | | | | |
| 16 | | END OF BOREHOLE (15.24 metres) Note: Not logged for geotechnical purposes. | | | | 680 |
| 17 | | | | | | 678 |
| 18 | | | | | | |
| 19 | | | | | | 676 |
| 20 | | | | | | |
| 21 | | | | | | 674 |
| 22 | | | | | | |
| 23 | | | | | | 672 |
| 24 | | | | | | |
| 25 | | | | | | |



Contractor: [REDACTED]

Completion Depth: 15.24 m

Drilling Rig Type: Track mounted

Start Date: 2020 July 22

Logged By: [REDACTED]

Completion Date: 2020 July 22

Reviewed By: [REDACTED]

Page 1 of 1