

HYDROGEOLOGIC LOG

BOREHOLE NO.

TW06-02

PURPOSE OF HOLE: Water Supply Well
 DRILLING METHOD: Air Rotary
 DRILLING DATE: September 16-19, 2006
 CONTRACTOR: [REDACTED]

GROUND ELEV.: 755 m-geod (approx.)
 CASING STICK UP: 1.0 m
 DEPTH TO STATIC: 6.210 m-bgl.
 LOCATION: Levich Drive

Depth (m)	Lithology	Comments	Well Installation Summary
0m			Circle Plate - lockable
1.5m	SAND & GRAVEL - some silt, fine to med. sand & gravel, moist, brown.		8" (200 mm) bentonite surface seal 4.6 m
9.8m	BEDROCK (GRANODIORITE) - competent	Static Water Level = 6.21 mbgl (October 20, 2006)	Bottom of 6 5/8" (168 mm) O.D. Steel Casing @ 12.2 m
42.7m	- Possible fracture @ 42.7 m-bg.		DRILLED OPEN HOLE 6" (152 mm)
61.0m	END OF HOLE		

O:\Whitehorse\Drawings\Whitehorse\1260000\1260009\Wise Copper Sub Water Supply\Fig 3_7REV.1.dwg [FIG 4] December 19, 2006 - 3:15pm [buyc]

CLIENT
 [REDACTED]

WHITEHORSE COPPER SUBDIVISION HYDROGEOLOGICAL ASSESSMENT FOR WATER SUPPLY-WHITEHORSE, YT.

WELL LOG TW06-02

[REDACTED]

DWN	CKD	REV
		0
DATE		
December 20, 2006		

Figure 4