BELLEVIEW SUBDIVISION		CLIENT: (BOREHOLE NO: 4561-17							
LOT #32		DRILL: JOHN DEERE 410 BACKHOE					PROJECT							
WATSON LAKE, YUKON														
	LE TYPE DISTURBED IN RECOVE													
BACK	FILL TYPE 🗾 BENTONITE 🛛 🔀 PEA GRAVE	L IIII SLOUGH	<u> </u>	<u> </u>	ROUT									
			Ш	SAMPLE NUMBER		BULK DENSITY (kg/m ³)		◆ CLAY (%) ◆ 20 40 60 80						
Depth (m)	SOIL		E TYPE	IUM	GROUND ICE DESCRIPTION	S	SPT (N)	• • •	GILT (%) ● 40 60 80		Depth (ft)		
epth	DESCRIPTION			Ш	AND				▲ S	AND (%) 🔺	.	epth		
ă			SAMPLI	MPI	COMMENTS	PLASTIC	M.C.		GR	40 60 80 AVEL (%)				
0	PEAT MOSS(PT)-root mat, and organic silt		0,	SA		20 4	0 60	80	20	40 60 80	0	0 _		
-	GRAVEL AND SAND(GP)-clean, with occasional		-											
	cobble 200 mm; subrounded to subangular, smooth gravel; coarse											_		
-	to medium grained sand; interbedded with medium bedded lenses of sand,											_		
-	lenses 100 mm to 150 mm thick;						• • • • •					_		
	damp; compact(est.); greyish brown											-		
-												-		
												_		
-	-with occasional lenses of coarse grained sand											-		
-	granie cana											_		
-				1				• • • • • • •				5_		
-												-		
												_		
- 2								: : :				-		
												_		
-												-		
-	-100 mm thick lens of iron oxide													
	stained and black gravel											_		
											1	┙╡		
				2								¥ -		
-				2				::::				-		
3												10_		
												_		
-												_		
												_		
-												_		
-			_									_		
[]														
_ 4	END OF TEST PIT 3.7 m									· · · · · · · · ·				
E	NOTE: 25 mm PVC standpipe installed											4		
	to 3.6 m											-		
-												-		
												15_		
												-		
												_		
5												16		
									LETION DEPTH: 3.7m					
		REVIEWED DT. DRAWING NO: 4561-						COMPLETE: 1986-08-12 17 Page 1 of 1						